TEST OF A THREE TON REFRIGERATING PLANT

BY A. J. BEERBAUM N. W. STRALE P. L. KEACHIE

ARMOUR INSTITUTE OF TECHNOLOGY

1912

621.5 B4



* i

AT 244 Beerbaum, A. J. Test of a three ton refrigerating plant

FOR USE IN LIBRARY ONLY

.

A State of States and S

ILLINOIS INSTITUTE OF TECHNOLOGY PAUL V. GALVIN LIBRARY 35 WEST 33RD STREET CHICAGO, IL 60616

TEST OF A THREE TON REFRIGERATING PLANT

A THESIS

PRESENTED BY

A.J. BEERBAUM N.W. STRALE P.L.KEACHIE

TO THE

PRESIDENT AND FACULTY

OF

ARMOUR INSTITUTE OF TECHNOLOGY

FOR THE DEGREE OF

BACHELOR OF SCIENCE IN MECHANICAL ENGINEERING

HAVING COMPLETED THE PRESCRIBED COURSE OF STUDY IN

MECHANICAL ENGINEERING

MAY 29, 1912

Dean of Cult: Studies Deare of Europer Steeders



TABLE OF CONTENTS.

.

142 1.

Introduction el.

ra I II.

Preparation for Tests.

Indicator Leducing	otions	 	.I .ge
Inculating Toxes		 	.I te i.
crddr;ær or et er .			
liteon condensing A:			
Changes in the lini	ng J, ste	 	.l. ge .t.

PAR III.

Tr ing out the Apparatusi je 6.

PALIT IV.

The Tests.

Licthol of 1	rocedu	re		 I a	re
Uutline of	Theor:			 	Je 11.
Discussion	• • • • •			 	he ld.
Samule Coly					
tumnary of	voras	e kesi	ulto	 	
Jurves					
Illustratic	ns	• • • • • •		 	
Data				 	
Drawings				 	

·

TEST OF A THREE-TON ELFRICELATING FLANT.

INTRODUCTION.

The subject of this report is an armoniacompression refrigerating plant of three tons refrigerating aspacity. The problem consists of a series of tests under different back pressures. This requires the taking of data relating to the efficiencies of the boiler, engine, and compressor, besiles a large number of observations of the temperatures and pressures at various points in the steam, water and ammonia lines.

Before proceeding with the test, a considerable amount of installation and orey ratory work was necessary. This consisted chiefly in the installation of a stear conformer and vacuum murp; the construction of reducing motions for the stear and complessor cylinders; the construction of a more ror measuring the annonia back pressure; changes and additions in the piping systems; the building of insulating boxes for the amnonia condenser and erpansion coils.

I ceneral view of the clant is shown in Plate I. Its essential lements are a 25 H.1. Brie Economic boiler; a 6" x 6" vertical compressor directconnected to a 6" x 6" horizontal engine; a Godble-tube ammonic compenser; Souble-tube expansion coils; an ammonia liquid receiver and an accumulator. The refrigerating equipment was furnished by the York Lanufacturing Company. A Wheeler surface condenser and a Marsh vacuum pump enable the engine to be run concensing, and a closed heater makes possible the preheating of the water to prevent too low a temperature being attained in the cooler or expansion coils.

The operation of the plant may be more clearly understood by following the automia, stear, and water mining through a complete cycle.

The compressed anmonia gas pusses from

the concressor through an oil separator into the outer tubes of the contensor. The amionia in the liquid state gravitates from the contensor into the resolver below. The liquid is then forced through the accumulator (or by-passes it) into the outer tubes of the cooling coils. Here it vaporizes, absorbing its latent heat from the water in the inner tubes, and the gas is drawn through the accumulator into the compressor cylinder, where it is again compressed, and the modess is remeated.

Water from the city cain is weighed and then fed into the boiler. Steam from the boiler flows into the main healer, which supplies the envine, heater, and auxiliaries. The exhaust steam from the engine passes either into the songenser of the sthogshere as desired, the exhaust from the cuxiliaries passing to the atnosphere.

Fresh water, instea of brine, is used in the expansion soils. Using to the shall vipe susplying water from the sity main, it was found necessary to have a concrete summ to maintain a sufficient sumply for operation. Tater is taken from the sump and forced through the ammonia condenser. From the ammonia condenser it may go to the cooler and then to the steam condenser, or go first to the steam cordenser and then to the cooler. In either case it may be sent through the leater before going to the cooler. After leiving the steam condenser or cooler, as the case may be, the water is weighed and returned to the sume. .

•

PREPARATION FOR TEST.

INDICATOR REDUCING MOTIONS.

Plate II shows the indicator reducing motion for the steam cylinder of the refrigerating machine. The pantographic linkage was used since it gives a perfect straight line motion to the point to which the indicator cord is attached. The distance moved by this point is also directly proportional to the distance moved by the point of attachment to the crosshead. The rulley and fork at "0" permit the proper adjustment of of the indicator cord passing to the indicator. The proper height of the linkage can be adjusted by moving the clamped rod "R" along the standard "S". All the parts except the small brass pulley are made of soft steel.

Plate III shows the reducing motion for the ammonia cylinder. The size of the linkage is the same as that for the steam cylinder. The position of the string can be adjusted by moving the rod "D" within the bearing "A".

INSULATING BOXES FOR COILS.

Plate IV shows the insulating box for the ammonia condenser. It is made of 7/8" tongued and grooved pine boards held together by 2 x 3/4" sticks. The top and bottom sections have slots at "A" and "B" which fit over the side sections. This construction permits the removal of the toy and sides in order to get at the coils. The space around the tubes is racked with mineral wool which reduces the massage of heat to the contents of the tubes.

Plate V shows the insulating box for the expansion colls. The construction is similar to that of the box for the conlenser.

M ROURY LANOLEPER.

Plate VI shows the mercury manometer which was constructed for measuring the ammonia back cressure on the congressor. By means of this manometer the pressure can be obtained with greater accuracy, than with the ordinary pressure guage and it also eliminates

a calibration. The hose-connections shown at the top could not be u.ed. One tap is left open to the atmosphere and into the other tap is screwed the pipe connected with the gas line returning to the compressor. The glass rods used are 5/8' outside diameter. With the exception of the aluminum back, all the parts had to be made of steel so as not to be affected by the ammonia. The manometer must losigned by Lr. T. . Libby of the bechanical Department.

STILL CUILDISING APPARATUS.

Flate VII shows the layout of the steam condensing a paratus. The contenser is a double flow surface contenser manufactured by the Theeler Condensor and Engineering Commany. There are 41 tubes in the first or lower mass and 53 in the second pass. The tubes are 1/2" inside diameter and 5/8" outside diameter with a length of 47 1/8'. The steam surface is 60.4 sq. ft. and the water surface 40.3 sq. ft. The condenser is supported by two 2 1/2" x 3/4" wrought iron supports imbedded 6" in the soncrete foundation. The condenser is used only in connection with the refrigerating machine in order to determine its steam consumption. The cooling water inlet may come from either the amonia condenser or the expansion coils as indicated on plate I. The Marsh vacuum pump has a 4" x 6" steam cylinder and 6" x 6" water cylinder.

SHANGES IN THE LIDING YEDELL.

In order that tests may be made with and without the use of the assumulator a by-pass connection was made as indicated on Filte I. The liquid ammonia from the receiver may pass directly to the expansion value or first pass through the accumulator coils where it would be cooled by the surrounding gas soming from the expansion soils. As formerly connected up, the liquid ammonia from the receiver would always have to pass through the accumulator on its may to the expansion coils.

.

Then the steam contenser was installed it was necessary to change the present water biping somewhat. There being very little space for more than one set of weighing tanks it was decided that the same water be used in the amnonia condenser. cooler, and steam condenser. As stated previously the water from the sump may take two routes. It may pass the amnonia condenser, through the heater. through the cooler and then through the steam condenser or after bassing through the ammonia condenser the water may go through the steam condenser. through the heater, and then through the cooler. 1 1/4" tees were inserted in the lines on each side of the condenser so that the steam conlenser could be operated independent of the rest of the apparatus.

TRYING OUT THE LEPARATUS.

The first attempt to try out the apparatus was made on Tednesday, may 1, 1912. On this obtained hand heads were discovered at the manhole and one of the handholes of the boiler, and the fire was drawn from the grate. These leaks were attended to and on Thursday the compressor was run for the purpose of placing the system under air pressure. The discharge pressure did not rise, however, and steps were taken to locate the leak. It was found that when the valve in the water outlet from the annonia condenser was closed, the pressure rose. This indicated a leak between the inner and annular space of the double tubes.

The anionia condenser was then taken apart, and the two lower inner tubes were found to be cracked, evidently due to the freezing of the water which was left in the coils during the winter. This water from the coils had gravitated into the receiver, about $2 \ 1/2$ being visible in the gauge glass. The water was drained out of the receiver and two new 1 1/4" tubes were put in place, new gashets being used.

On the same day the low pressure side was pumped up to an air pressure of 160 lbs. gauge (142 lbs. corrected) and left there until the next day. After this run, leaks at the safety value and at one of the joints in the steam leads from the boiler were remained.

On Friday, May 3, it was found that the low pressure system had held the pressure of the day before. The safety valve was set by the boiler inspector at 38 lbs. gauge (corrected). The gauge reading was 93 lbs., the intended blow-off pressure being 95 lbs. gauge.

After the amnonia condenser had been repaired, the high pressure system was tested out with sir pressure and found satisfactory. On the .

.

following Norlay a small charge of annonia whe fed into the system, while under air crossure. The joints were then tried out for leaks by the sulphur test. Sticks of sulphur were lighted and moved around each joint. There ammonia was escaping, dense fumes of sal-ammoniac would form. The only leaks discovered were at the flanged joints. The bolts on all the flanges were then drawn up and further application of the sulphur sticks gave no indication of objectionable leaks.

The system was now given a larger charge of amnonia and on Duesday, since no leaks appeared, the remainder of the charge was put in. nakine a total of ...bout 150 lbs. of amuonia. Then charging the system the outlet valve on the receiver and all the valves between the receiver and the expansion valve were closed. Then the blind flange just below the expansion valve (see Plate I) was removed and a connection made to the ammonia drum. The gas who then drawn out of the drug, through the cooler and into the comressor. From the compressor the gas passed to the amionia condenser where it was liquified. It then collected in the receiver below. The system new contained a mixture of amonia and dir. The dir was removed by attaching small pet cocks to the surge rives on the contenser and cooler. To these cools rubber tubing was fastened. The other ends of the tubes were placed into a bucket of water. The cumonia cas being highly soluble in water dissolved, while the air escared in bubbles to the surface of the water. Then no more bubbles appeared the system was free of air.

Indicator cards taken from the compressor cylinder were narrow and extended and indicated invroper working of the discharge and inlet valves. The compressor cylinder head was removed and the valves taken out and thoroughly cloaned. The cards obtained now were still unsufisfactory and the valves were again removed and also the piston. Eurred edges were fund on some of the piston rings and these were filed smooth. In better card was now obtained, although it was not the conven-

tional shape of an ammonia compressor card.

The indicator cards from the steam cylinder were satisfactory, showing a sut-off on both ends of about two-thirds of the stroke. The machine did not run very steadily at first, but as it continued running, conditions is proved and the groan in the compressor cylinder was no longer audible.

The circulating pump and vacuum pump were found to operate stisfactorily. In charging the system the steam condenser was not used, the enhaust from the engine and circulating pump going to the stmosphere.

THE TESTS.

The original intention was to run the refrigerating machine condensing and to run tests with and without the use of the accumulator. When prepared to begin the tests, leaks were discovered at the inlet and outlet of the water heater and it was very difficult to get at the joints and solder then. It was therefore decided that the heater be cut out entirely and so the fittings at the heater were broken and the pipe rising from the amonia condenser to the heater wis connected directly with the water inlet to the cooler. Furthermore, it was found that the range of temperature produced in the cooler was not very great and consecuently when using the steam condenser, the water leaving the cooler and running back into the sump was wite warm and this water entering the amonia condenser required a higher pressure to contense the amonia than was thought desirable. For this reason the steam condenser was not used and the ensine exhausted to the atmosphere. After having started the first run on Thursday evening, lay 9, a severe leak was discovered around the thermometer up on the liquid ammonia outlet of the accumulator. Drawing up the thermometer sum did not stop the leak. Since our time for testing was limited we decided to run all our tests without the use of the accumulator. The mercury manometer for the use of measuring the ammonia back ressure could not be used since the required length of glass tubing could not be obtained in due time, so it was found necessary to use the saure.

The first actual run was started on Friday morning, May 10, at 1:00 o'clock. The average back pressure was 37.6 lis. (corrected) Readings of the temperatures and precourse shown on the running log were taken every fifteen minutes for three hous. Indicator cards on the engine and compressor were also taken. The revolutions per minute were obtained from the continuous courter.

(

.

An attempt was made to make the next run with 60 lbs. back cressule but dwing to the inperfect valve action it was impossible to maintain that pressure any great length of time. It was then decided to make a run with 30 lbs. back pressure. This run was started at 6:30 A.M. on the same day. Observations were taken every fifteen minutes. Then the third reading was taken it was noticed that the continuous counter was not recording properly, and all previous readings of the counter for this test had to be referred. This necessitated counting the strokes for a minute to obtain the revolutions per minute. For some unknown reason the engine stopped a little after 9:00 L.M. and the run stopped half an hour earlier.

The cards taken from the amionia compressor were very poor and showed that the discharge valve was not corring properly. The cylinder head was removed and a discharge valve put in. The valve on the steam cylinder was tightened because from the cards it seemed as though the valve was loose. The engine was then started up again and appeared to run better than before except that one of the bearings became too warm and had to be loosened. The valves appeared to be working better than before but the cards still showed that it was not absolutely right.

The third run was made Friday evening from 8:00 to 11:00 o'clock with results as shown on the running log.

The test was resumed on Saturday morning at 11:00 o'clock. Using to the lack of the it was desided to make runs of two hours duration. Four runs were made with the back pressures at 11.4 lbs., 22.4 lbs., 2 lbs., and 5 .9 lbs. (corrected values)

Between every run it was found necessary to let the air out of the system by running rubber tubing from the purge outlets into a busket of water.

The circulating water, during a run, became very warm and this necessitated the runping of the water from the sump and putting in fresh water.

After finishing the test, cards were taken from the concressor and engine cylinders with the engine running at low speeds.

OUTLINE OF THEOHY.

The boiler efficiency would be the same for all the number. Hence in order to obtain as long a period of fuel consumption as possible, the efficiency was figured by confilering all seven runs as one and using the average values of all pressures and temperatures. Since the thermodynamic efficiency of an injector is cractically 100% the heat absorbed by the boiler is the amount required to evaporate the cold supply water temperature, then the factor of e-vaporation $F (t_{\rm c} - 32)$

Let W = water evaporated per lb. of soal . Then the c nivelent evaporation from and at 212° F=7 x F. Then the heat absorbed by boiler per lb. of soal: $W_{1}(t-t_{p}+32)$

Efficiency of boiler and grate $\frac{7}{1\pi} \frac{(\lambda - t_{\pm}^2 C_{\pm})}{C_{\pm}^2}$

The ideal refrigerating machine is a reversible engine operating in a Carnot cycle in a reverse direction from that of a steam or any other heat engine. The collectency of a Carnot engine when operating as a heat engine \pm rise, where H = the source of heat and H₂ that going H to the refrigerator. If the engine be run ackward the "thermodynamic efficiency" would be $\Xi_{12} = \Xi_{22}^{-12}$ where T = the absolute temperature of H H to the absolute temperature of the source of the sou

The thermodynamic efficiency of an

engine working in a Surnit cycle is less than one, hence that in the refrigerating **cycle** must liwage be greater than unity.

The object of the refrigerating process is the repoval of the heat I in the cooler, so that this may be consilered the adeful work. Hence the actual efficiency of a refrigerating machine $\underline{\mathbf{K}}_{\mathbf{1}} = \underline{\mathbf{E}}_{\mathbf{2}}$; where $\underline{\mathbf{F}}_{\mathbf{2}} = \mathbb{Q}(\mathbf{t}_{\mathbf{1}} - \mathbf{t}_{\mathbf{1}})$, Q being the water pass-A Ve in: through the cooler per binute and t, and t, are respectively the inlet and notlet temperatures. We H.I. of the concressor sylinder and A W, its heat equivalent. The above efficiency gives a result greater than unity because the or oria receives heat from the ster in the scoler and rejects heat into the condenser. Thit is, the work to be done by the commensor is not the mechanical e vivulent of refrigeration, but only that necessary to supply the difference between the heat rejeated by the aconia into the contenser and that received in the coller.

The heat removed by the condenser = K=Q(t_-t_) where d condensing water very indicate and t, and t = the outlet and inlet temperature. respectively.

erch, A, (t.-t.) where A, a jacket water per birdte and t and t. the outlet and imlet temperatures reapectively.

The refrireration of usity in tons per twenty on hours $\frac{C(t_1-t_2) \times 24 \times 60}{288,000}$ 288,000 is the helting effect of the ton of ise in 1.2.3.

The thermal efficiency of the plant referred to the scale ile equals the refrigeration produced mer lb. of scal divided by the J.J. value of a lb. of scal as fired.

The heat belance of the refrigerating s, ten is as follows: E-AR2 kin, where A the heat abstracted (refrigeration); '2" -2. of concressor sylinder; Reheat abstracted in the concluser; r, total sum of losses by radiation and convection, etc.

· ·

DIJOUSSION.

The only steam concumption determined in the test was that of the engine and disulting sum together. In order to 3 termine the water rate of the engine running noncondensing the pump would have to be connected up with the condenser and its team concurption determined. This consumption subtracted from the water fact to the beiler could give the water rate of the engine. This determine for could have be and the best of time.

The boiler and grite efficiency is very low. To think this is writh due to the large excess of from sime through the entry since there are no ash doors and the operator is very large. For a greater much of the time, however, sheet metal who set up in front of this opening. The boiler was running at about 60, of its normal rating and the efficiency is probably lower at this load.

The speed of the ongine in the first run looks doubtfal. At the beginning of the decond run it was discovered that the continuous counter was not recording properly. The speed recorded was too how. In all probability the Line of 9.7 in the first run is too how. This would account for the low J. J. of the steam splinder and the high refrigeration produced per minute per 7.1. of both eplinders.

In several runs the heat recoved by the condensor is less than the cold produced, thich is contrary to theory and to results obtained in good practice.

In all the runs easert the seventh the heat removed in the jacket rater is greater than the indicated work of the consideror. This is certainly due to the very your operation of the values.

increases ith increase of had mersure up to a

maximum and ther ecreases.


Jurve 14 shows the tonkage to increase with increase of hack ressure as it should. There must however, be a tarming point in the curve because when the back pressure because and to the contensing pressure there would be no explosion and therfore no relation.

decrease with increase of back pressure we it should.

Jurve (5 shows that the terper bare of the ras entering the couler (after passing the expansion valve) increases with the increase of back pressure. This would be appeared since the encansion is decreased and hence a less from in temperature.

The shape of card chick should be obtained from the compressor when operating properly is shown in the annexed digram. The vork required to open the compressor values is indicated by small projections at the measure and suction lines. The effect of clearance is shown by a sloping of the curve "I". According to Siebel the companion and compression serves of the indicator cards obtained in the test show is to the culver leaded very healy. During the entire the of the test only the satisfactory of devene obtained.


on the bole we consider the results of the test very unsattificatory. The lost exhanical efficiency is due to the leaving of the values and these should be reground or to their white and the entire machine should be given a theread overheading. We also think that some of the poir results were due to the incorrect readings of most of the thermometers. The ther operatings of most of the guinst a standard thermometer which had been calibrated at the U.S. Bureau of Standards, a few years before.







and gamma as as off a sty the start of the start <u>Entransferrans</u>


























*/s Discharge Preis (sevje, 6- Jack H.P.=122 Mech EH:=48.6% 2 F.P.M. 24% Disch Press. (kage) 26% 350k H.P.= 2.08 Mach. EH:=49.6% Disch. Press. Back " H.R=23.6 Mech Eff = 53.2% AMMONIA CYLINDER CARDS SLOWER SPEEDS



,



Compressor

Expansion Coils with Accomulator Behind

.



Expansion Coils showing Mineral Wool Used as Insulating Material. Circulating Pump

Steam Cylinder



Steam Gylinder Steam bondenser & Vacuum Pump



Close View of Engine



NH3 Condenser

Accumulator Receiver



Steam Condenser & Vacuvm Pump

Compressor

2=2: 47.5% State: 12.5%	afelle.	HERE	Hick Con	14.41	1000	Calle -	544	(apple)	Sec. Or				12.2	10-84	
	1940	241 - 2	Reported 1	÷		145	10		- 1 - 1 - 1		-	1	3	Ewen	12.5
	Mer.	141	(1)/2			120		200	÷.	-	· Me		1615	1.5	
	They a	11	Sec.			2.11	100	202	it's a			22	100	1992	
									1 - 						
						2	1216	A.				1000	110	Malendi.	246
							11:21	41.				and the second	1000	1120	180
							1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				12.11	1.95 184 1.33 140	Alle 1	6 114	the state
			1				12.23				120 m	1000	6 103	12.2	A.
												6.01 1.13	692	2012	14
		42							<u></u>			Tille. Con	14.15 . 01	6 9000	12/2/12/20
													11 (A)	11 2	No.
						= -	-					1997 (A.S.)	11 11/1	100 m	14/3/2
									· ··· ·		:			16/2/	122
						1	1.4	a a					19	2000	1997 1997
							् <u>र</u> ्थः इ.स.		324 32		1.3	15 Carlo	196	1. Contraction	Silling .
						,				11/1		ufile'	11 11 48 18 W	1911 (1921 427 1923) 292 (1921 1923)	1602
				÷ 1							1.2	12/2	1.2	201	1133
			-										Alley Statul 2 7		Pinister
									1				2/10		Souther
			ستدر ستر 	1 1 1	10 L 10 10 10		15		1.15	200			12	13. Mar 18. 20	35.
						1945		11/1		15	5	11			100
and a subscription of the									- <u></u>			14		2000	
							1.5					1.201	the second	E.	Cel 1
								i jan ana		1			12 %		and the
						 	1		-	1					in the
a Elaberta La				New York	1.202.3			1.2.4.		197	14.2			1363	1.010



to our	2				15 101	65 4 m	Ser.		16.6	10/10/1		A Contraction of the second se	11	U. M. S.	101.10		
N	11162	1	1000		121.0			11 15 1	16 6 M	S. Mary	1 1 10	1 della	11. 111	0.11/11/0	- M		
	LIGEL DE PERIN DE PERIN		WELLENG !	TADAT DADAT OL JIDE	HARDEN THE INC.	GUERNICH VIII (2)	DETA.T DETA.T DETA.T	EEGNTE. SETTER	-1 · ///=/***/**	4300 4977 213 F	2053) 25(2)	LIND LOGLOU DECID	LET DE			and the second sec	······
		-	5/				ange Station Station		120	<u>92'</u> (193 '	20 <u>39</u>	- 1987 - J	3/5	103) 103 103	2 16 <u>7</u> 3		(e)(f)
	2. 3.1	-								have a l			to be at in tail if the		190	116 2011	
						Ş.		V				11/20	11.11		11 in	HE ai	
	,	, =: 			-				· · · · · · · · · · · · · · · · · · ·			1		1 	1	12	14.25
						129		2	1								
	,			2	10 20			*								14 J.Z.	(EEE)
							· · · · · · · · ·						1943	141	14	11. 100.	11101
		- 1.41 								7 2 2 2		<u>}</u>			(1997)	141	inest.
		·					<u></u>							No.	12		
		¥.		·		15											
			postante est			· · · · · · · · · · · · · · · · · · ·				u telu E Terri			63	-	tana dina tana tana tana tana		1 ¹
		1. 1. 1.				198	100				the life		1982	17	Property of the second		(Meile)
1 25 1		And A CONTRACT OF		12410	AN EW	24/25-3/10	100				100	R. Martin			13442	Elles Links	1.dan



		11.00 H. 200 1.00 1.00 1.000	14.16 110 110 10 10 MIN	14.6 M. 1.14. 4. 24.66	1 12 12 1 Hall		15 [In [10] w [1996	1.1. 700 1.115 25011 1996	111 600 600 4000 2000	1. 1. 1. m 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	1 1800 an 120 March	121 121 1211 - 1217	146 300 42	14 Cell 1077 - 10 - 157060	18 715 This Cours Willing	15 716 742 1990 4 20 1 20 1
			10% 7%				101	1496 891	11.10	16-51 200		1647 1616	128 34	1416 66	12351 1143	16.30 1636
				1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					12	1/185		1193 (311)	1. 1186 W.	6 166 610	15 Minkel 600	CANTER TEL
			 						102/03	2	1 10 1				12 The Mar	2 11/1 16
						67 23	1	1 1 × 1 3	" " " " " " " " " " " " " " " " " " "	<u>, , , , , , , , , , , , , , , , , , , </u>		1997		16 19 10	06 (25)	Carlo V
												120	1 (0) 10	10. 19.23	1992 SAUS	Price Calles Ve
								121-1	2 12	1	The state	13:6	1913 040	115 30	1248 924	1691 1691
			S.,			~ ~ ~	27	<u>1</u>				- Ali	100	Solution (28)	100	8 EV105 6112
		1. Star 1. Sta					1 Startes	1. 20 115 × 1 12.8 1	· · · · · · · · · · · · · · · · · · ·	6.4. West 2010 13	14 3723		18 14 20 DE	1990 1990 1990 1990 1990 1990 1990 1990	lade Venile Stitte Belle	1015 10400 - 56 07 10 15100
	2200 0202 1254 17700															1. 2. 2. 2. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.




		0	1=1/1/109 6 DOANIN <u>NO9</u> 	09/01	19 Partill	States -		(UECO)	eephil	STER.	Contra (13)		ENER	
	-	12.00					1		•					100
	1. States		100000 (055) 1005130	1921	(ECE)				a),	22	1/3	100	SU SU	16:40 (243)
		10	LETRIJO DE TOST	(Bill)	(383)	Ster.		ing.	÷.	Elle .	1511	N.	134	Chill .
	.9	N. I	-29705 19705	1115	200	1		4.0	202	E.	6.6	des.	de las	600
		(0) 12	2 IN 100 2 IN 10 139	êtî)	÷.	2	i lej		and a	W.	1552	E.	11	19191
	1 m	4 156 14 0 14 1	LETING DEGREDNES	÷.	134	1990	1	.34/1	iille:	-Mil		14	Alle.	Itest
	1219	(B)	15/7/57 2099525 No.3	1. 45	12	11	ė	2	14	140		144	The second	10.5
	White	1000	199552431105	1.45		(Clife		100	112(2)		1 5	1.24.02	700	ling
1111	110		LEFELAD LEFTELS			ninin ini Sec	13	3	E	3	(C)		1941	EGN
12 (0) (0)	25.25	lat.	LET TOLD LET TOLD	199	17/		1	lin.	-	Ŵ	1 81	14	11	100
In la	112	百	HEITHING NECONEMINICO	1.20	l 2	i Seri	1 No.	5	1	111	iller.	M.L.		The second
1111	11954	1/ 1/	LETINIT: MERCHERNSOF		14	-	1	(i.)		(exist)	44	EE.	1000	
Ð		M.C.	24=1741/11() 1.5. 1.5. 1.5.		7.12. L		1425	1000	194	100	1.00	102	112	199
10/01		24	137 : 137 : SPICA	<u></u>	12		1.34	- <u>~</u>		16	610)	25	620	title Citil
Nec.	1000	ال ترکنینی	BALLES 19		125			1998	Sec. 1	2452	12.42	1992	1923	alle -
HE I	3	W.	DAGA SA	1			19.12	- The	1	18		H.	16:6	All I
	SPUCE		ALLE ALLE		1929		1. 1. 1	HALLS .	Child P	hell 1	100	11:00	11. 1109	1.003 1961
	21212	=/	FINIS ED WOFLE	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	1	5.(6)	1. 1. 1. 1	50 11	No.	1. 197	-51	10	10th	NON T
	1		EL UGILE UTUR		1		- <u>S</u>						Sett 2	76
	11/4/2	1.7	NALGAG DI NALGAG DI NALGA NALDIN				1					1	ACCEN S	
	and a	Ge	III URELE	llater come		N.S.	. 20	<i>0</i> (0.11	- Stall	1910	13	6.6	- Co
INV.		ġ	ALERIAL CALLER	100	- CER	129	224			1	12	Estim.	Set .	1212 130
010	in C.C.	1		Sec.	1828	No.	66 140	÷. (†	125	the sea	1975	6.6 124	÷.	100
in la	14-21				C.	(all)	66	4/1/10	36	50	(inc)	60	all'	12.1
1 de	15	inter :						4 2					12.20	
0117	11.200	-	HSH	1		. 4			1		1		- Contraction	
01	1112		7100	Set.			:	la series de la		3			Equ.	1.
	1 H	1	ZWIL	110	196	17	199	(Pride	19	S.C.	220	and the second	600	聖御




		و ری د	5 1.NAOJ 6AO AMILHOJ	1605	1765	the fi	CARE S	100	i try b	1564	1164	alles,	- 3)	ingen Digen
	2 00 1 1	14	III.INGUIE	(bist)	1112	- Keller	an -	h to the	2692	10	4	U.S.C.	123998	Ser Con
			ENTRA NORSA ERCEG	116	191	16	- 11-	1112-	71631.	THUS	All .	1.50	The	in in
13-11-14 M			12571110 8257005	The	1912	- Mi	13 La	n.	4	41.	ull.	÷٩.	101	100
		11/14	21577-11 2157920	9.62	Ett.	The .	111	ith.	-112	5.15	题	Will.	6,66	GHE?
		101	LETURO DESKEDKOR	6/16	199	in the second	Bill:	630	Elli.	3	10		616	SW2
	a la	A MINT ONYI	127217	19th	1800 1861	ido -	"Man	1293	340	1992	100	lants BE	12124 61 4 6165	Earlie
11 M	245	R	2551805 1305555581(97)	1716 1116	ĝį,	315	1 201	12	ЭЦ.	#12	10	W.	2.665 27044 (012 7441 (304) 3007 7246 11422 7124	TEU
	114 12 12 12 12 12 12 12 12 12 12 12		LETLINO E0933PL/MCA	1000	WEN.	alle.	12/11/2	h Gay	162	M.C.	166	6/15/14/15/14/16	iltere	1975
	(Red.		1.277.400 2.577.000	A.	pić.	Tille.	198	5711.	Shell.	and the second	i alter	129C	NEU	TPale
Same M	NRYE.	in.	25,719,17 25,709,00	Bill	310% pre	199	Stor.	The .	200	Шŗ-	119	e)[[5]	669	7.CM
12/01	1151	A. T. E. G.	11317/100 13151301168	- All		eggi	311	i de la	(îi)	11.	Elč.	111	GUE	1110
3	N.	1.15	13/1.87 339/130/10)	- Me	Tellin .	Î.Σε.	Gille.	5	Ser.	Sell.	1982	₩,	11:51	1181
		W	LERILIC	120	1.000	100	1991	Heart.	316	M.	in the	56 110	(0)]2	16Vel
	11111	1.00	LETTER LECITOR	Alise.	.50% /10%	4.5	E.	(j)(j)	191	- 111	die	E.	13010	Gille
18	5/1/	1	ELE DI LOND DI LELE	GHE.	1372		16	iller-	965		214 123	1996 63 894	2000	2019
<u> </u>	1002	þ	REGENT RIS	EE.	5721	1 10	12	- State	48	63	alle.	BE	about .	(UCA
	CKOND.	il.	- 1000 - 2022 921920210: 345	102	Well.	104	180	1.91	PM.	11:34	All a	GAN	(LER	1 Mille
101	PR0		31419413 01 4175113	tille.		5	6.5	513			No.	(lui)	118255	1991
	11/16	10	251270 1512020 1512020 15125-151 1520 251250							-		1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1		15 2001 Street
1-100	01.01M	5	ביילא אלצוב בובאוטסינט אלבנק שפידוס <u>ב</u>	10 100 100	199	100 - 34 E	(8) 250 ft	11.9 43.7	1413, 2500 194		All Miles	1269 710 4	His mer Flog	113 Sec. 15 112
00	TTEN		2322/11 232/11 172/10/6	in lie	0	14	the second	1.6	1 site	- Per			1020	1000
11 121 11	VELGHTS V		USH USH KSH					2				lind Ciffe		all littles &
120	D)C)		7002	122	1 2 4		1			1		leit-	in the second se	EST.
		1123	JWI I	000	311	als	100	el in		015.10	Steel State	die la	Stirles	inelo vice




and the second second			TLNNOD SNONKILINDD	90 WOR	liger in	10 100	223 2334	1) 11020	19:5	Mile	W.AL		6400	Valler.
and a		2.9	ELELIO2UZ	218:50	16.Cm	N.H.		ST. Bell	1012	2	15	S.H.	a 103 tail	
			Elilan Moder ECELER	712	10	÷.	Î	- Allina	A. H.	1 Million	(11/2)	2	1016	1
In .	Sec. 1		15/1600) 197(399)	72		(all	111	Eller Star	210	HR.	24	S.	Fille	1.12
54	No.	(1119)	457141 937099	206	A.C.	640	1182	STE	de d	Gulton Contraction	-1016	1030	ZURE	1
and a		101	LEMPLOO EEDNEIONOO	SIE	Me	Stall .	- 180 -	16	N.	1	113.00	The	THU .	
	S.	WWW	LERING SECKER(195)	illeft,	(iji) -	(Gi)	1699	All's	10	33	223	1115	A.M.	
	1221	1a	LETARA EGGENEDIDO	-	141.	Ţ.W.	181	ų.	10		(39)	lites.	14249	1
No. of Street, or Stre	122 6		SERVICO GEOGECUNOS	Ref S	History History	14.(0)	æ	10	11520)	166	in the	12111-1215	11:00 19:00	1
18.41	1992	¥	DEAPLAG DETIGOR	112.	1112	B	212	3	1911	13	i fills	6	121	
nr (0). (0). MM	11:3-	- Contraction	4200000 35170000	12 AN		192	AU.	191	18	1	199	test.	(Allen)	-
TOF 1	115 14	(0)	SECTIONS	July -	.GIL	W.	STU.	. 8	M	111	11/2)	-10	1156	
	R	175	21=114717 21=53:550:400	(54)	(e)L	10	ĨĒ		101	1	3	Stal.	11/1 1/16	0
N.C.	1 2 - 2 - A	We	1277300 15121010	100	Elle !!	Refer	11111	6711	Ell'	633	20	aller .	all a	1
2411		1	LEMART	El al	Ell		(0)(5			÷	8	:117	CARDO I	-
AN. C	S. C.	2	SUSPACED	BER	The second	33;60	26.0	A.S.	15/2 (3)3/2	340	38	220	221,40	-
<u>E</u>	122		TROD. GR	00	(PO)	20	and the	Sing	(c)	17/2	20	6	all all	1
-X-	EGAD.	1	20109 119321 Del 119321	Sig	Hillin.	10	11.25		they a	Rell	(17)	.8	Web (
Ser.	Peler -		SHERE MERE	elle I	13.	Ba	Shore	66	121	Gut.	63	int.	and a	
and the second	32.10	¢.	DELLONI SELLONDO									3.10	1	
. The second	11/1/25	1	ロヨン エスタン TT TIGA JILIM			1		1. 1.				3 91110		1
1 and		G	SING MIELE	60	elle l	B	143	B	(iB)	etter -	6201	H.H.	- Miles	
1111C	3	2	ELERNE OTTO MELLIG	25-60	34E	E.C.	A.	EX11	2012 (DB)	246 610	and the second s	Ref .	E CES	
In Contra	Till'			150		1				W.H.			12/2	
1/2	W.		And MG	- All	-181	in)	40	.9	3	8	9	8	Caller.	
Cold States	1651		OF ER	1.							-	Colles :		, .
Colla .	Aleda	in a	HG.Y	ê					1			R.		1.1
101	1.de		7603	21 3		1 11 14 1	in the second	1						
			3KIL	in the	(the	Sille	El Sto	States	ade	SUE	1940	Contes	des	iner de






FRIDSPIERTE := えるののシンテラ ふまん SAMPLE STRAM ICARDS CO BB. SERING ANGENE REPAIRS SAMPLE AMARCHA CALD 130 43 332130 12 3.03 3:06] 79 : 742 9.6 97/ 2.55 763 762 Ī. 11 3.06 3.06 2 E 2 44 يق العظيمة مج 2.33 まりョ 37/7 6 Pro

and a second device of the second second




HE GEL ATTINGE PHER HOOLONE TER. SAMALE STEAMA CARDS 30 40 3721110 AVERAGE FR. 2006 = 130113 ADERAGE NHE DISCHARGE ALES BUT DE DIS BACA - m = 27/3 - AFRIDEPHERIE LINE - Aleguerra Zerra GAMPLE FUNDIONDA ÉREDE 100 45. EFRING RUN NO. 2 STERN Orlander したがいうまだ HEAD END <u>- ÉRANA ÉNE</u> ·法主任 (1) (1) REAL MELIGITH The state of the second se 2.3313.21 3.20 3.231 ,654 2.13 2.33 3.30 7031



HE TRADERIESSE LINE Factor toria Face of SAMPLE STEAM CARDS COLE SPRING AVERAGE REPARS SIGNA 13 DISCH 92 PRESS (GAUGE)=1398 = 25A. AFRICASPHIERO LINE HESDLOVE BERD O SAMPLE AMINDMA CARD 100 13, 372000 RUN NO. 3: STEAM CYLINDER Winds CYL ANDER HEAD END CRANT 1233.61 1LEGYETCH AREA SERVETIC MO.O. State I 140 11292575 · 7/46/ 3.3C 2.96 3.11 3.96 . 7.3.9 3.04 70.7 2.13 9.19 745 778 1.00 2.33 302 200 3117 3.). TTE 5. O.7 739 3110 2.29 00 228 うちろ 319 7/3/9) 2.44 3.10 1613 3. 016 3.16 3:00 754 2.33 3.00 783 30 4 37 3.16 3/3/2 77/22 19.23 1. 30 3,00 00 2.36 2:45 3.21 1313 7/07:50 5.14 1294 793 235 3.51 3.46 15 2.40 390 1.124 30 2.50 2,30 300 334 3.13 324 すうラ 145 243 2.971 2.27 sE 7/C 577 TS Fri in 113-14

The second se


FRISSASSASSAS LANE REALL THE TERO . W SECTE STEAR CARDS ED LE SEEME AVERAGE. 周月 283 年1月日年 ハハトト ゴイシモン・キュア・アスティーション(CAUSE)=1343 EMAG TEPPINSBUERDE LINGE 435020775Z236 & SANNE SHARANS 6.2.20 100 LE SPENNE STEAM. ONLINEER INFAS CALINDER. HIZAD END 重わう A.F.F.A. LENGTH WIDO. SIBER! 1.289.57 Bost .623 243 3.12 1970 192 2.02 674 ショッチ 63 201 あり草 *\$*.5 286 民间是 ゆます 243 3.12 201 2.01 Bill 215 :687 312 12 3.37 1231 30 2.04 633 33041-675 3.14 323 2:45 2:05 3.10 0199 00 1.96 246




र के देवर देवर के दिन्द्र के Skiele Start Daard se de cum la ್ರ್ಯಾಂ . Alemo 15 3.29 15 2.39 30 <u>7.3</u>9 45 <u>2.</u>39 . . J. 13 10 2.34 3073 16 333 5,50 2,29 3-15 2,33 4:00 230





Stan. 1 通用のほう ATES . 1.3.5. M 18T 00 16 30 1.75 2.35 \$ ME 1. 7.3 1.39 1 1.50 A .














































liteles for Altarpung 1945 no Frido 29 Mayotres AL 3% -The n and HALLE SECTION. NDENSER 1912 DLATE DE Beerbaum - Mesebie - Strath











LATE


























	SUM Providence		1612 1612	Service of the servic	11/20			
WINBER	BER DE RUN		<i>M</i>	S.	14- 1-	رون	1 <u>1</u>	~
1 Gool per hour 1			- de al al	Reference of		19 July 19	S. S. S. Line	
2 Feederstand		C. Start	10000	Section I	EHGW 3	1900-14	TOP PE	1.000
S. Comes and	and a state of the second s	10	New Service	20151	The are	1.82	2012	750
A State New Sec.					15.03	240	1000 C	
	and services and the services of the services	Will Describe	NOUN.	West and	lover were work were	NGRI	11355	11000
					- 11-12 			
	a construction of the design of the second	1. 1 6000	Ser.	「「「「「「「「「」」」	and the second	and the second		and the second
Section 2 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -			Service Service		F.G. 2.	- Friend	1 A 10(2)	
and a second	and the second for a state of the	the second second	a second	a transfer trans	a contraction of the second	Section States		Les and the
A State of the sta							1	
		1999	10 10	1. 18 2				1 12
ER BUNCT IN THE L	A State of the second				1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	199	and the second	1. C. C. M.
Star Maria	and the second	19. 19. 19. 19. 19. 19. 19. 19. 19. 19.						and a strategy
Mer Maria and		1.511	1012	147 134	Ne.			5 - C - C - C - C - C - C - C - C - C -
				1. 1. 1. 1.				CAN TEND
					10 E.C.			
					1 4 52 C			
				1. 1. 1.				
				N.C.				1
	and the second				342			1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1
			5. 5. 2			1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1		
			Service of the service	1. 1. 1. 1. L	なななない			



